

L-PNT-COM Technical Datasheet

COMMANDA

Matt Latex Undercoat

DESCRIPTION:

Commanda is matt emulsion paint based on special acrylic copolymers for use in all types of atmospheres. Can be used as a high quality undercoat or as an economic top coat for surfaces that are often repainted (schools, hospitals etc.) Suitable for use on all types of surfaces.

PHYSICAL DATA:

Binder : Acrylic copolymer
Pigments : Titanium dioxide (rutile)

Appearance : Flat

Colours : White and colors

No. of Components : One Specific gravity : 1.65 Solids by volume : 75%

Drying times at 30°C : Touch Dry : 30 minutes

Hard Dry : 24 hours Recoat : 120 minutes

Flash Point : Non Flammable

APPLICATION DATA:

Application Method : Brush - Roller – Air Spray – Airless Spray

Type of Thinner : Water

Percentage of Thinner : Brush and Roller : 7 - 15%

Air Spray : 15 – 25 % Airless Spray : 10 – 20 %

Dry Film Thickness per Coat : 30 Microns Theo. Coverage at 30 Microns DFT : $5-7 \text{ m}^2/\text{kg}$

REMARKS:

- 1. Stir well before use
- 2. Clean all tools with water
- 3. Surface treatment should be accomplished before use of **Commanda**.

SHELF LIFE AND STORAGE:

12 months from production date if stored in its original tightly closed container in a dry place away from direct sunlight and excessive heat.

Conforms to Ministry Directive # 181 of year 1996

Disclaimer: The information & data contained herein are given in good faith but without warranty. We recommend that before using our products, the customer should make his/her own tests to determine the suitability of the products for his/her own purpose under his/her operating conditions. As the circumstances under which our products are stored, handled and used are beyond our control, we cannot assume any responsibility for their use by the customers.