



# CREPILUX

## Textured Coating Smooth – Extra fine

### DESCRIPTION :

**Crepilux** is novelty water based latex coating designed to add grandeur to individual's household property and is suitable for both interior and exterior concrete and plaster surfaces. It is an air drying coating devoid of lime and cement. A commendable feature of this product is that it gives high film thickness per coat without any cracking problems under severe climatic conditions. The longevity of this coating coupled with labor saving application is the outcome of effective combination of its constituents.

### PHYSICAL DATA:

Binder	:	Acrylic copolymer
Pigments	:	Titanium dioxide and / or color pigments
Appearance	:	Flat! 'Superfine texture
Colors	:	White and Colors
No. of Components	:	One
Specific gravity	:	Approx. 1.70
Solids by volume	:	Approx. 65 %
Drying times at 30°C	:	Touch Dry : 1 hours
	:	Hard Dry : 6 hours
	:	Recoat : 24 hours
Flash Point	:	Non Flammable

### APPLICATION DATA:

Application method	:	Roller
Type of Thinner	:	Water
Percentage of Thinner	:	10 – 15 % by volume
Coverage	:	1 - 1.5 m <sup>2</sup> /kg or 1.7-2.5 m <sup>2</sup> /liter

Special pressed pattern can be achieved by using a plastic roller before the sprayed coating dries completely.

### REMARKS:

**Crepilux** provides an ideal decorative finish to precast concrete areas. It is suitable for application on gypsum board and plaster. Especially developed for humid climate areas, providing long life without maintenance.

### SHELF LIFE AND STORAGE:

12 months from production date if stored in its original tightly closed container in a dry place away from direct sunlight and excessive heat.

*Disclaimer: The information & data contained herein are given in good faith but without warranty. We recommend that before using our products, the customer should make his/her own tests to determine the suitability of the products for his/her own purpose under his/her operating conditions. As the circumstances under which our products are stored, handled and used are beyond our control, we cannot assume any responsibility for their use by the customers.*

#### شركة سياج للكيماويات

الإدارة: ٨٧١ شارع بورسعيد - الوايلي - القاهرة - ج.م.ع.  
تليفون: ٢٤٨٢٨٥٦٦ - ٢٤٨٢٨٦٠ - ٢٤٨٥٨٣٥٠ - فاكس: ٢٣٨٣٣٦٤ (٢٠٢)  
محمول: ٠١٠ ٥٢٨٨١٣ / ١٤ - محمول مبيعات ١٢٣٨٧٨٥٢٦ (٢٠٢)  
www.slagchemicals.com - بريد إلكتروني: info@slagchemicals.com - انترنت:



#### Slag Chemicals Company

871 Port Said Street- El Waily - Cairo - EGYPT  
Tel: +(202) 24828620- 24828566- 24858350 -Fax: +(202) 26833364  
Co.Mobile: +(202) 010 5386813/14- Sales Mobile: +(202) 012 26878526  
E-mail: info@slagchemicals.com - Website: www.slagchemicals.com