

L-PNT-T-MNC

# MONOCOUCHE

# Textured Coating Fine to Medium

**Technical Datasheet** 

### **DESCRIPTION:**

**Monocouche** is novelty water based latex coating designed for adding grandeur to individual's household property and is suitable for both interior and exterior concrete and plaster surfaces. It is an air drying coating devoid of lime and cement. A commendable feature of this product is that it gives high film thickness per coat without any cracking problems under severe climatic conditions. The longevity of this coating coupled with labor saving application is the outcome of effective combination of its constituents.

#### PHYSICAL DATA:

Binder Pigments Appearance Colours No. of Components Specific gravity Solids by volume Drying times at 30°C	<ul> <li>Acrylic copolymer</li> <li>Titanium dioxide and / or colour pigments and selected aggregates</li> <li>Flat'! Fine to medium textured finish</li> <li>White and colors</li> <li>One</li> <li>Approx'1.7</li> <li>Approx. 77%</li> <li>Touch Dry : 40 minutes Hard Dry : 2 - 4 hours Recoat : 24 hours</li> </ul>
Flash Point	: Non Flammable
APPLICATION DATA:	

Application method	:	Roller – Air Spray – Airless Spray
Type of Thinner	:	Water
Percentage of Thinner	:	Max. 5%
Coverage	:	1- 1.5 m²/kg or 1.7 – 2.5 m²/L

Special pressed pattern can be achieved by using a plastic roller before the sprayed coating dries completely. To prolong drying time use **Okay Retarder**.

#### **REMARKS:**

**Monocouche** provides an ideal decorative finish to precast concrete areas. It is suitable for application on gypsum board and plaster. Especially developed for humid climate areas, providing long life without maintenance. For better coverage apply one coat of latex undercoat instead of latex sealer.

# NOTE :

A coat of water based varnish is recommended to give glossy appearance. This will also help minimize dust collection and to give excellent gloss and colour retention property to the coating under exterior/interior exposure.

# **SHELF LIFE AND STORAGE:**

12 months from production date if stored in its original tightly closed container in a dry place away from direct sunlight and excessive heat.

Disclaimer: The information & data contained herein are given in good faith but without warranty. We recommend that before using our products, the customer should make his/her own tests to determine the suitability of the products for his/her own purpose under his/her operating conditions. As the circumstances under which our products are stored, handled and used are beyond our control, we cannot assume any responsibility for their use by the customers.



الإداريّ: ۲۸۱ شارع بور سعيد – الرايلي – القاهرة – جمع. تليفون: ۲۲۵۲۸۵۲۱ - ۲۶۸۸۵۲۰ (۲۰۰) – فاكس: ۲۲۳۲۲۱ (۲۰۲)+ مصول: ۲۵ / ۲۸۱۸۰۲ - ۲۰ (۲۰۲) – مصول مييعات ۲۲۷۸۸۷۲۲۱ - ۲۰۱)+ بريد إلكتروني: info@siagchemicals.com – انترنت: www.siagchemicals.com



671 Port Said Street- El Wally - Catro – EGYPT 871 Port Said Street- El Wally - Catro – EGYPT Tel: +(202) 24828620- 24828656- 24858350 -Fax: +(202) 26833364 Co.Moblie: +(202) 010 5386813/14- Sales Moblie: +(202) 012 26878526 E-mall: info@siagchemicals.com - Webstle: www.siagchemicals.com