



OKAY HAMMERTONE Hammertone Finish Paint

DESCRIPTION :

Okay Hammertone is a premium quality modified alkyd high gloss top coat designed to provide a hammered finish that hides surface imperfections. **Okay Hammertone** provides a novelty finish, gives a unique pattern and obscures the unevenness of the surface. It eliminates the use of putty on uneven surface. It is fast drying, easy to spray and has excellent adhesion to various metal substrates. When applied over a suitable primer it gives good water and corrosion resistance. The pattern and gloss of **Okay Hammertone** are long lasting.

PHYSICAL DATA:

Binder	: Modified alkyd resin
Pigments	: Aluminum, paste and /or colour pigments
Appearance	: Gloss
Colour	: As desired
Number of components	: One
Specific gravity	: Approx. 1.00
Solids by volume	: Approx. 50%
Drying times at 30°C	: Dust dry : 1 hour : Hard dry : 6 hours
Flash point	: 26 °C

APPLICATION DATA:

Application method	: Air spray
Type of thinner	: Mineral Spirit
Percentage of thinner	: 5% max. by volume
Dry film thickness per coat	: 35 microns
Theor. Coverage at 35 Microns DFT	: 14.2m ² /liter

REMARKS:

Painting is to be done by applying a mist coat followed immediately by a full coat. No overcoating is to be done.

SHELF LIFE AND STORAGE:

12 months from production date if stored in its original tightly closed container in a dry place away from direct sunlight and excessive heat.

Disclaimer: The information & data contained herein are given in good faith but without warranty. We recommend that before using our products, the customer should make his/her own tests to determine the suitability of the products for his/her own purpose under his/her operating conditions. As the circumstances under which our products are stored, handled and used are beyond our control, we cannot assume any responsibility for their use by the customers.

