



ALKYWOOD 400

Wood and Wall Primer

DESCRIPTION :

Alkywood 400 is a modified alkyd based primer for wood, cement, plaster, concrete and gypsum board surfaces. It has excellent covering capacity, hiding power and adhesion. Ideally suitable for exterior and interior use. It has very good sealing and priming properties and sandable when hard dry.

PHYSICAL DATA:

Binder	:	Modified alkyd resin
Pigments	:	Rutile titanium dioxide and fillers
Appearance	:	Flat
Colour	:	White
Number of components	:	One
Specific gravity	:	Approx. 1.4
Solids by volume	:	Approx. 50%
Drying times at 30°C	:	Dust dry : approx. 30 minutes Hard dry : approx. 6 hours Next coat : overnight
Flash point	:	39°C

APPLICATION DATA:

Application method	:	Airless spray, Air spray, Roller and Brush
Airless spray data	:	Nozzle 0.015", pressure 150 kg/cm ²
Type of thinner	:	Mineral Spirit
Percentage of Thinner	:	Airless spray : nil Air spray : 10% max. by volume Brush : 5% max. by volume
Dry film thickness per coat	:	40 microns
Theo. Coverage at 40 microns DFT	:	12.5 m ² /litre

REMARKS:

Surface Preparation :

- Clean wood surface after sanding down.
- Clean all plaster and block board walls.
- For absorbent substrates apply one coat of **Alkywood 400** 20% thinned.

Subsequent Coats :

- Two coats of enamel or latex paint (Gloss, Semi-gloss and Flat) suitable for interior or exterior use.
- Not to be applied over fresh cementations surface with high alkalinity.

SHELF LIFE AND STORAGE

12 months from production date if stored in its original tightly closed container in a dry place away from direct sunlight and excessive heat.

Disclaimer: The information & data contained herein are given in good faith but without warranty. We recommend that before using our products, the customer should make his/her own tests to determine the suitability of the products for his/her own purpose under his/her operating





conditions. As the circumstances under which our products are stored, handled and used are beyond our control, we cannot assume any responsibility for their use by the customers.

شركة سياج للكيماويات

الإدارة: ٨٧١ شارع بورسعيد - الوايلي - القاهرة - ج.م.ع.
تليفون: ٢٤٨٢٨٥٦٦ - ٢٤٨٢٨٦٢٠ - ٢٤٨٥٨٣٥٠ - فاكس: ٢٣٨٣٣٣٤ (٢٠٢)
محمول: ١٤ / ٥٢٨٨١٣ / ٠١٠ (٢٠٢) - محمول مبيعات ١٢٢٦٨٧٨٥٢٦ (٢٠٢)
بريد إلكتروني: info@siagchemicals.com - انترنت: www.siagchemicals.com



SIAG Chemicals Company

871 Port Said Street- El Waily - Cairo - EGYPT
Tel: +(202) 24828620- 24828566- 24858350 -Fax: +(202) 26833364
Co.Mobile: +(202) 010 5386813/14- Sales Mobile: +(202) 012 26878526
E-mail: info@siagchemicals.com - Website: www.siagchemicals.com