



SUPER PRIMASTIC

Water Based Latex Putty

DESCRIPTION :

Super Primastic is a high quality water based acrylic putty with high filling properties. It is suitable for use on exterior and interior cement, ordinary and pre-cast concrete and other surfaces to repair surface defects, restore and polish surfaces before painting. It provides a thick coat after only one application. It exhibits excellent flow as well as a good balance between hardness and elasticity.

PHYSICAL DATA:

Binder	:	Acrylic copolymer
Pigments	:	Titanium dioxide (rutile) + active fillers
Appearance	:	Flat
Colours	:	White and colors
No. of Components	:	One
Specific gravity	:	1.7
Solids by volume	:	70%
Drying times at 30°C	:	Touch Dry : 40 minutes Hard Dry : 24 hours Recoat : 120 minutes
Flash Point	:	Non Flammable

APPLICATION DATA:

Application method	:	Putty Knife – Trowel
Type of Thinner	:	Water
Percentage of Thinner	:	5%
Dry Film Thickness per Coat	:	100 Microns
Theo. Coverage at 30 Microns DFT	:	1.5 – 2 m ² /kg

REMARKS:

- Among this putty's best qualities is its adhesion power to many types of undercoats and top coats due to its combination of active fillers.
- Surfaces should be clean and free from dust and oil. Surfaces should be treated with an suitable sealer such as **Sealerprime** before application of putty.
- Surfaces should be lightly sanded after application of putty with appropriate sandpaper.

SHELF LIFE AND STORAGE:

12 months from production date if stored in its original tightly closed container in a dry place away from direct sunlight and excessive heat.

E.S.S # 6623/2008

Disclaimer: The information & data contained herein are given in good faith but without warranty. We recommend that before using our products, the customer should make his/her own tests to determine the suitability of the products for his/her own purpose under his/her operating conditions. As the circumstances under which our products are stored, handled and used are beyond our control, we cannot assume any responsibility for their use by the customers.

شركة سياج للكيماويات

الإدارة: ٨٧١ شارع بورسعيد - الوايلي - القاهرة - ج.م.ع.
تليفون: ٢٤٨٢٨٠٦٦ - ٢٤٨٢٨١٢٠ - ٢٤٨٠٨٣٥٠ - فاكس: ٢٣٨٣٣٣٤ (٢٠٢)
محمول: ٠١٤ ٥٢٨٨١٣ / ١٤ (٢٠٢) - محمول مبيعات ١٢٣٦٨٧٨٥٢٦ (٢٠٢)
بريد إلكتروني: info@siagchemicals.com - انترنت: www.siagchemicals.com



SIAG Chemicals Company

871 Port Said Street- El Waily - Cairo - EGYPT
Tel: +(202) 24828620- 24828566- 24858350 -Fax: +(202) 26833364
Co.Mobile: +(202) 010 5386813/14- Sales Mobile: +(202) 012 26878526
E-mail: info@siagchemicals.com - Website: www.siagchemicals.com